



Low VOC Cleaner

6405SP/01

6405SP/01 Low VOC Cleaner is a superior waterborne surface cleaner used for removing most contaminations including wax and grease, mold release agents and sanding dust.

6405SP/01 Low VOC Cleaner can be used on a wide variety of substrates including; bare metal, plastics, primers, etc.

6405SP/01 has a VOC of 0.4 and is compliant with most VOC regulations nationwide.



Features:

Benefits:

Low VOC.....Compliant with most VOC regulations nationwide
 Universal.....Cleans all substrates

Directions for Use

6405SP/01 0.4 VOC Cleaner:



- Apply a generous amount of 6405SP/01 on the surface with a clean cloth or a hand held spray bottle and wipe the surface.
- The initial application will float contaminants to the surface, and the second wipe using a separate clean dry cloth, will remove contaminants.
- For maximum results, wipe the surface dry while it is still wet, using a clean white cloth in one direction. This will eliminate the smearing of contaminants. Be sure to change rags frequently.
- Never let the cleaner dry on the surface.
- Use 6405SP/01 before and after sanding.

Technical Data:

Color	Clear
VOC lbs./US gal.	0.41 VOC

6405SP/01

Low VOC Cleaner

Important: Refer to SDS for safety guidelines. Use in a well ventilated area with appropriate Personal Protective Equipment (PPE) to protect eyes, skin, and respiratory system.

See Safety Data Sheet and Labels for additional safety information and handling instructions.

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION - US (412) 434-4515; CANADA (514) 645-1320; Mexico 01-800-00-21-400
Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein. If you require technical assistance, please call us toll-free 800/323-6593.



The World's Finest Coating For Architectural Signage

760 Pittsburgh Drive
Delaware, OH 43015
Toll Free: 800/323-6593
Toll Free FAX: 800/947-0377